

Econometrics 1 *Applied Econometrics with R*

Lecture 2: Basics of R

黄嘉平

中国经济特区研究中心 讲师

办公室：文科楼1726

E-mail: huangjp@szu.edu.cn

Tel: (0755) 2695 0548

Office hour: Mon./Tue. 13:00-14:00

R installation

See <http://huangjp.szu.edu.cn/Rinstall.html>


1. Download and install R
2. Download and install RStudio
3. Install packages

An introduction to R

R: A Language and Environment for Statistical Computing and Graphics

- <https://www.r-project.org/>
- R is free to use (open source under GNU license)
- R can be run on Windows/MacOS/Unix systems
- R is interactive
- R has many packages that are ready for use
- You can develop your own tools with R





命令窗口

变量窗口

绘图窗口等

Play with R

R is a high level calculator

```
> 1 + 2  
[1] 3
```

```
> 2^24  
[1] 16777216
```

```
> factorial(5)  
[1] 120
```

```
> log(exp(sin(pi/4)^2) * exp(cos(pi/4)^2))  
[1] 1
```

- Try the following commands (functions):

`log()`, `exp()`, `sin()`, `cos()`, `tan()`,
`sign()`, `sqrt()`, `abs()`, `min()`, `max()`

- Use `?` or `help()` to see help documents of commands, for example

`?sign`, `help(sign)`

- Calculate the value of $\phi(2.5)$, where

$$\phi(x) = \frac{1}{\sqrt{2\pi}} e^{-\frac{1}{2}x^2}$$

Variable

- Assignment operator “<-”

```
> x <- 25
```

```
> y <- 3
```

```
> x * y
```

- Characters that can be used in a variable name:
A~Z, a~z, 0~9, _
- A variable name should start with a letter

Vector

- `c()`

```
> x <- c(2, 3.5, -3, 6.4, 21.9)
```

- The *i*-th element of a vector

```
> x[3]
```

- The length of a vector

```
> length(x)
```

Understand the difference between “`()`” and “`[]`”:

- “`()`” is used with a function
- “`[]`” is used with a variable (vector or matrix)

Try arithmetic with vectors

- `+`, `-`, `*`, `/`, `^`, `sqrt()`, `exp()`, `log()`
- `mean()`, `var()`, `prod()`
- `sort()`, `order()`
- Calculate unbiased sample variance using

$$s^2 = \frac{1}{n-1} \sum_{i=1}^n (x_i - \bar{x})^2$$

and compare your result with that of `var()`

Generating patterned vectors

- How to generate a vector (1, 2, 3, 4, ..., 20)

```
> x <- c(1, 2, 3, 4, 5, 6, 7, 8, 9, 10,  
11, 12, 13, 14, 15, 16, 17, 18, 19, 20)
```

```
> x <- 1:20
```

- Use `seq()`, `rep()`

```
> x <- seq(from = 1, to = 2, by = 0.1)
```

```
> y <- rep(x, times = 5)
```

Matrix

- Create a matrix from a vector

```
> x <- 1:12
```

```
> y <- matrix(x, nrow = 3, ncol = 4)
```

- Elements of a matrix

```
> y[2, 3]
```

```
> y[2, ]
```

```
> y[, 4]
```

```
> y[3, c(1, 3)]
```

Basic matrix algebra

- Try `+`, `-`, `*`, `/`, `^`, `sqrt()`, `exp()`, `log()` with a matrix

- Create a matrix $z = \begin{pmatrix} 1 & 5 \\ 2 & 6 \end{pmatrix}$

- Matrix multiplication

```
> z %*% z
```

- Transpose

```
> t(z)
```